

## Product datasheet:

# Cable glands Progress® stainless steel A2 for high temperature applications

## Long entry thread metric

### Approval type: Progress S2 HT

- One-piece sealing insert
- not overall length insulated
- 1 = Metric coarse-pitch thread (with VDE Testreport)



|                        |                       |
|------------------------|-----------------------|
| <b>Article number:</b> | <b>1100.50.96.420</b> |
| E-No:                  | 121613908             |
| EAN:                   | 7611614133782         |
| Packaging quantity:    | 10                    |

### Dimensions / Form

|                  |         |
|------------------|---------|
| Thread:          | M50x1.5 |
| Spanner size:    | 55 mm   |
| Dimension H:     | 34 mm   |
| Thread length L: | 14 mm   |

### Connections / Entries

|                      |                        |
|----------------------|------------------------|
| Min. clamping range: | 37 mm                  |
| Max. clamping range: | 42 mm                  |
| clamp technology:    | Compression technology |

### Features

|                |        |
|----------------|--------|
| Thread type:   | metric |
| Thread length: | long   |

### Approvals / Certifications

|                                  |                       |
|----------------------------------|-----------------------|
| Protection class:                | IP69                  |
| Protection class with condition: | IP 68 (10 bar) / IP69 |
| VDE:                             | Yes                   |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 200 °C |



Assembly instructions



Certificates



Planning data