

Product datasheet:

Cable glands Progress® EMC easyCONNECT nickel-plated brass with contact spring

Short entry thread metric

Approval type: Progress EMV easyCONNECT

- Two-piece sealing insert
- not overall length insulated
- 1 = One-piece sealing insert
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- Entry thread Pg and NPT



Article number:	1083.50
E-No:	121063008
EAN:	7611614290546
Packaging quantity:	10

Dimensions / Form

Thread:	M50x1.5
Spanner size:	55 mm
Dimension H:	42 mm
Thread length L:	9 mm

Connections / Entries


Min. clamping range:	37 mm
Max. clamping range:	42 mm
Clamping range with inlet min.:	33 mm
Clamping range with inlet max.:	37 mm
clamp technology:	Compression technology
Contact:	Contact spring

Features

Properties:	For a quick and safe installation of partially dismantled cables as well as thoroughly shielded cables
Thread type:	metric
Thread length:	short

Approvals / Certifications

Protection class:	IP69
Protection class with condition:	IP 68 (10 bar) / IP69
VDE:	Yes



Assembly instructions



Certificates



Planning data

Product datasheet:

Storage / Installation / Operation

Minimum operating temperature:	-60 °C
Maximum operating temperature:	100 °C