

Product datasheet:

Cable glands Progress® EMC nickel-plated brass with contact sleeve

Short entry thread metric

Approval type: Progress MS EMV

- One-piece sealing insert
- not overall length insulated
- 1 = Metric coarse-pitch thread (with VDE Testreport)
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.



Article number: **1080.50.410**

E-No: 121072818

EAN: 7611614119557

Packaging quantity: 10

Dimensions / Form

Thread: M50x1.5

Spanner size: 55 mm

Dimension H: 36 mm

Thread length L: 9 mm

Connections / Entries

Min. clamping range: 37 mm

Max. clamping range: 41 mm

clamp technology: Compression technology

Contact: Contact sleeve

Safety / Properties

Shielded design (EMC): Yes

Features

Properties: Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland

Thread type: metric

Thread length: short


Approvals / Certifications

Protection class: IP69

Protection class with condition: IP 68 (10 bar) / IP69

VDE: Yes

Storage / Installation / Operation



Product datasheet:

Minimum operating temperature:	-40 °C
Maximum operating temperature:	100 °C



Assembly instructions



Certificates



Planning data