

Product datasheet:

Cable glands Progress® EMC nickel-plated brass with contact sleeve

Short entry thread metric

Approval type: Progress MS EMV

- One-piece sealing insert
- not overall length insulated
- 1 = Metric coarse-pitch thread (with VDE Testreport)
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.



Article number: **1080.85.700**

EAN: 7611614235202

Packaging quantity: 1

Price group: 520

Dimensions / Form

Thread: M85x2.0

Spanner size: 95 mm

Dimension H: 45 mm

Thread length L: 18 mm

Connections / Entries

Min. clamping range: 63 mm

Max. clamping range: 70 mm

clamp technology: Compression technology

Contact: Contact sleeve

Safety / Properties

Shielded design (EMC): Yes

Features

Properties: Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland

Thread type: metric

Thread length: short


Approvals / Certifications

Protection class: IP69

Protection class with condition: IP 68 (10 bar) / IP69

Storage / Installation / Operation

Minimum operating temperature: -40 °C



Assembly instructions



Planning data

Product datasheet:

Maximum operating temperature: 100 °C
