

## Product datasheet:

# Cable glands Progress® EMC nickel-plated brass with contact sleeve

## Long entry thread Pg

### Approval type: Progress MS EMV

- One-piece sealing insert
- not overall length insulated
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.



|                        |                    |
|------------------------|--------------------|
| <b>Article number:</b> | <b>1180.11.085</b> |
| E-No:                  | 121038208          |
| EAN:                   | 7611614115238      |
| Packaging quantity:    | 50                 |

### Dimensions / Form

|                  |       |
|------------------|-------|
| Thread:          | Pg 11 |
| Spanner size:    | 21 mm |
| Dimension H:     | 23 mm |
| Thread length L: | 10 mm |

### Connections / Entries

|                      |                        |
|----------------------|------------------------|
| Min. clamping range: | 5.5 mm                 |
| Max. clamping range: | 8.5 mm                 |
| clamp technology:    | Compression technology |
| Contact:             | Contact sleeve         |

### Safety / Properties

|                        |     |
|------------------------|-----|
| Shielded design (EMC): | Yes |
|------------------------|-----|

### Features

|                |                                                                                                                    |
|----------------|--------------------------------------------------------------------------------------------------------------------|
| Properties:    | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Thread type:   | Pg                                                                                                                 |
| Thread length: | long                                                                                                               |

### Approvals / Certifications

|                                  |                       |
|----------------------------------|-----------------------|
| Protection class:                | IP69                  |
| Protection class with condition: | IP 68 (10 bar) / IP69 |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 100 °C |



Assembly instructions



Planning data