

## Product datasheet:

# Cable glands Progress® EMC nickel-plated brass with contact sleeve for high temperature applications

## Short entry thread Pg

- One-piece sealing insert
- not overall length insulated



|                        |                          |
|------------------------|--------------------------|
| <b>Article number:</b> | <b>GD 1080.21.91.160</b> |
| EAN:                   | 7611614233673            |
| Packaging quantity:    | 25                       |
| Price group:           | 520                      |

### Dimensions / Form

|                  |        |
|------------------|--------|
| Thread:          | Pg 21  |
| Spanner size:    | 30 mm  |
| Dimension H:     | 30 mm  |
| Thread length L: | 7.5 mm |

### Connections / Entries

|                      |                        |
|----------------------|------------------------|
| Min. clamping range: | 13 mm                  |
| Max. clamping range: | 16 mm                  |
| clamp technology:    | Compression technology |
| Contact:             | Contact sleeve         |

### Safety / Properties

|                        |     |
|------------------------|-----|
| Shielded design (EMC): | Yes |
|------------------------|-----|

### Features


|                |                                                                                                                    |
|----------------|--------------------------------------------------------------------------------------------------------------------|
| Properties:    | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Thread type:   | Pg                                                                                                                 |
| Thread length: | short                                                                                                              |

### Approvals / Certifications

|                                  |                       |
|----------------------------------|-----------------------|
| Protection class:                | IP69                  |
| Protection class with condition: | IP 68 (10 bar) / IP69 |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 200 °C |



Assembly instructions



Planning data