

Product datasheet:

Cable glands Progress® EMC nickel-plated brass with antikink spring

Short entry thread metric

Approval type: Progress MS EMV FKN

- One-piece sealing insert
- not overall length insulated
- 1 = Metric coarse-pitch thread (with VDE Testreport)
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- Long entry thread



Article number:  **1080.10.52.040**

E-No: 121782208

EAN: 7611614195520

Packaging quantity: 10

Dimensions / Form

Thread:	M10x1.5
Spanner size:	13 mm
Dimension H:	54 mm
Thread length L:	5 mm

Connections / Entries

Min. clamping range:	3 mm
Max. clamping range:	4 mm
clamp technology:	Compression technology

Safety / Properties

Shielded design (EMC):	Yes
------------------------	-----

Features


Properties:	Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland
Thread type:	metric
Thread length:	short

Approvals / Certifications

Protection class:	IP69
Protection class with condition:	IP 68 (10 bar) / IP69

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	100 °C



Assembly instructions



Certificates



Planning data