

Product datasheet:

Cable glands Progress® EMC nickel-plated brass with antikink spring

Short entry thread metric

Approval type: Progress MS EMV FKN

- One-piece sealing insert
- not overall length insulated
- 1 = Metric coarse-pitch thread (with VDE Testreport)
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- Long entry thread



Article number:  **1080.12.52.075**

E-No: 121782318

EAN: 7611614195681

Packaging quantity: 10

Dimensions / Form

Thread: M12x1.5

Spanner size: 15 mm

Dimension H: 60 mm

Thread length L: 5 mm

Connections / Entries

Min. clamping range: 6 mm

Max. clamping range: 7.5 mm

clamp technology: Compression technology

Safety / Properties

Shielded design (EMC): Yes

Features

Properties: Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland

Thread type: metric

Thread length: short

Approvals / Certifications


Protection class: IP69

Protection class with condition: IP 68 (10 bar) / IP69

VDE: Yes

Storage / Installation / Operation

Minimum operating temperature: -40 °C



Assembly instructions



Certificates



Planning data

Product datasheet:

Maximum operating temperature:

100 °C
