

Product datasheet:

Cable glands Progress® EMC powerCONNECT nickel-plated brass

Short entry thread metric

Approval type: Progress EMV powerCONNECT

- Two-piece sealing insert
- not overall length insulated
- 1 = One-piece sealing insert
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- Stainless steel A2 or A4
- Entry thread Pg and NPT



Article number: **1084.63**

EAN: 7611614312644

Packaging quantity: 5

Price group: 520

Dimensions / Form

Thread: M63x1.5

Spanner size: 70 mm

Dimension H: 49 mm

Thread length L: 10 mm

Connections / Entries

Min. clamping range: 46 mm

Max. clamping range: 52 mm

Clamping range with inlet min.: 40 mm

Clamping range with inlet max.: 46 mm

clamp technology: Compression technology

Contact: Press sleeve

Features

Properties: For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance.
Compact design

Thread type: metric


Thread length: short

Approvals / Certifications

Protection class: IP69

Protection class with condition: IP 68 (10 bar) / IP69

VDE: Yes



Assembly instructions



Certificates



Planning data

Product datasheet:

Storage / Installation / Operation

Minimum operating temperature:	-60 °C
Maximum operating temperature:	100 °C