

Product datasheet:

Cable glands Progress® EMC powerCONNECT nickel-plated brass

Short entry thread metric

Approval type: Progress EMV powerCONNECT

- Two-piece sealing insert
- not overall length insulated
- 1 = One-piece sealing insert
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- Stainless steel A2 or A4
- Entry thread Pg and NPT



Article number:	1084.75
E-No:	121063018
EAN:	7611614312620
Packaging quantity:	1

Dimensions / Form

Thread:	M75x1.5
Spanner size:	80 mm
Dimension H:	51 mm
Thread length L:	11 mm

Connections / Entries


Min. clamping range:	56 mm
Max. clamping range:	63 mm
Clamping range with inlet min.:	50 mm
Clamping range with inlet max.:	56 mm
clamp technology:	Compression technology
Contact:	Press sleeve

Features

Properties:	For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance. Compact design
Thread type:	metric
Thread length:	short

Approvals / Certifications

Protection class:	IP69
Protection class with condition:	IP 68 (10 bar) / IP69
VDE:	Yes



Assembly instructions



Certificates



Planning data

Product datasheet:

Storage / Installation / Operation

Minimum operating temperature:	-60 °C
Maximum operating temperature:	100 °C