

Product datasheet:

Cable glands Progress® EMC powerCONNECT nickel-plated brass

Short entry thread metric

Approval type: Progress EMV powerCONNECT

- Two-piece sealing insert
- not overall length insulated
- 1 = One-piece sealing insert
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- Stainless steel A2 or A4
- Entry thread Pg and NPT



Article number:  **1084.80.650**

E-No: 121063128

EAN: 7611614312651

Packaging quantity: 1


Dimensions / Form

Thread: M80x2.0

Spanner size: 95 mm

Dimension H: 58 mm

Thread length L: 12 mm



Connections / Entries

Min. clamping range: 58 mm

Max. clamping range: 65 mm

clamp technology: Compression technology

Contact: Press sleeve



Features

Properties: For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance. Compact design

Thread type: metric

Thread length: short



Assembly instructions



Certificates

Approvals / Certifications

Protection class: IP69

Protection class with condition: IP 68 (10 bar) / IP69

VDE: Yes



Planning data

Storage / Installation / Operation

Minimum operating temperature: -60 °C

Product datasheet:

Maximum operating temperature: 100 °C
