

## Product datasheet:

# Cable glands Progress® EMC powerCONNECT nickel-plated brass

## Long entry thread metric

### Approval type: Progress EMV powerCONNECT

- Two-piece sealing insert
- not overall length insulated
- 1 = One-piece sealing insert
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- Stainless steel A2 or A4
- Entry thread Pg and NPT



**Article number:** **1184.32**

**EAN:** 7611614312705

**Packaging quantity:** 25

**Price group:** 520

### Dimensions / Form

**Thread:** M32x1.5

**Spanner size:** 36 mm

**Dimension H:** 38.5 mm

**Thread length L:** 13 mm

### Connections / Entries

**Min. clamping range:** 21 mm

**Max. clamping range:** 25.5 mm

**Clamping range with inlet min.:** 17 mm

**Clamping range with inlet max.:** 21 mm

**clamp technology:** Compression technology

**Contact:** Press sleeve

### Features

**Properties:** For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance. Compact design

**Thread type:** metric


**Thread length:** long

### Approvals / Certifications

**Protection class:** IP69

**Protection class with condition:** IP 68 (10 bar) / IP69

**VDE:** Yes



Assembly instructions



Certificates



Planning data

## Product datasheet:

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -60 °C |
| Maximum operating temperature: | 100 °C |