

## Product datasheet:

# Cable glands Progress® EMC powerCONNECT nickel-plated brass

## Long entry thread metric

### Approval type: Progress EMV powerCONNECT

- Two-piece sealing insert
- not overall length insulated
- 1 = One-piece sealing insert
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- Stainless steel A2 or A4
- Entry thread Pg and NPT



**Article number:**  **1184.80.650**

E-No: 121083128

EAN: 7611614312736

Packaging quantity: 1


### Dimensions / Form

Thread: M80x2.0

Spanner size: 95 mm

Dimension H: 58 mm

Thread length L: 18 mm



### Connections / Entries

Min. clamping range: 58 mm

Max. clamping range: 65 mm

clamp technology: Compression technology

Contact: Press sleeve

### Features

Properties: For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance. Compact design

Thread type: metric

Thread length: long

### Approvals / Certifications

Protection class: IP69

Protection class with condition: IP 68 (10 bar) / IP69

VDE: Yes

### Storage / Installation / Operation

Minimum operating temperature: -60 °C



Assembly instructions



Certificates



Planning data

## Product datasheet:

Maximum operating temperature:

100 °C

---