

Product datasheet:

Cable glands Progress® EMC Series 85 nickel-plated brass with collet chuck

Entry thread metric

Approval type: Progress EMV Serie 85

- Two-piece sealing insert
- not overall length insulated
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- Important: To provide the best possible protection for the cable shield and the cable, it is necessary to install a copper EMC tape.



Article number: **1000.63.85.440**


EAN: 7611614217840

Packaging quantity: 1

Price group: 520

Dimensions / Form

Thread:	M63x1.5
Spanner size:	70 mm
Dimension H:	78 mm
Dimension X:	26 mm
Thread length L:	15 mm



Connections / Entries

Min. clamping range:	46 mm
Max. clamping range:	52 mm
Clamping range with inlet min.:	40 mm
Clamping range with inlet max.:	46 mm
clamp technology:	Compression technology
Contact:	collet

Safety / Properties

Shielded design (EMC):	Yes
------------------------	-----

Features

Properties:	For high leakage currents, concentric shield contact with minimal transfer resistances and transfer impedances
Thread type:	metric

Approvals / Certifications

Protection class:	IP69
Protection class with condition:	IP 68 (10 bar) / IP69



Assembly instructions



Certificates



Planning data

Product datasheet:

VDE:	Yes
------	-----

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
--------------------------------	--------

Maximum operating temperature:	100 °C
--------------------------------	--------