

Product datasheet:

Cable glands Progress® EMC Series 85 nickel-plated brass with collet chuck

Entry thread Pg

- Two-piece sealing insert
- not overall length insulated
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- Important: To provide the best possible protection for the cable shield and the cable, it is necessary to install a copper EMC tape.
- Further dimensions upon request



Article number: **1000.29.85.250**

EAN: 7611614217925

Packaging quantity: 5

Price group: 520

Dimensions / Form


Thread: Pg 29

Spanner size: 46 mm

Dimension H: 68 mm

Dimension X: 24 mm

Thread length L: 10 mm



Connections / Entries

Min. clamping range: 28.5 mm

Max. clamping range: 33 mm

Clamping range with inlet min.: 24 mm

Clamping range with inlet max.: 28.5 mm

clamp technology: Compression technology

Contact: collet

Safety / Properties

Shielded design (EMC): Yes

Features

Properties: For high leakage currents, concentric shield contact with minimal transfer resistances and transfer impedances

Thread type: Pg

Approvals / Certifications

Protection class: IP69

Protection class with condition: IP 68 (10 bar) / IP69



Assembly instructions



Planning data

Product datasheet:

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	100 °C