

Product datasheet:

Cable glands Progress® EMC Series 85 nickel-plated brass with collet chuck

Entry thread Pg

- Two-piece sealing insert
- not overall length insulated
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- Important: To provide the best possible protection for the cable shield and the cable, it is necessary to install a copper EMC tape.
- Further dimensions upon request



Article number:  **1000.29.85.250**

EAN: 7611614217925

Packaging quantity: 5

Dimensions / Form

Thread:	Pg 29
Spanner size:	46 mm
Dimension H:	68 mm
Dimension X:	24 mm
Thread length L:	10 mm

Connections / Entries

Min. clamping range:	28.5 mm
Max. clamping range:	33 mm
Clamping range with inlet min.:	24 mm
Clamping range with inlet max.:	28.5 mm
clamp technology:	Compression technology
Contact:	collet

Safety / Properties


Shielded design (EMC):	Yes
------------------------	-----

Features

Properties:	For high leakage currents, concentric shield contact with minimal transfer resistances and transfer impedances
Thread type:	Pg

Approvals / Certifications

Protection class:	IP69
Protection class with condition:	IP 68 (10 bar) / IP69



Assembly instructions



Planning data

Product datasheet:

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	100 °C