

Product datasheet:

Splittable Frame, size 16

Divisible frame Series 1910 for cables with and without connectors

· Set of 4 stainless steel AISI304 fastening screws with black Dacromet finishing



Article number: **1910.16**

EAN: 7611614501291

Packaging quantity: 10

Dimensions / Form

Installation opening (wall/ceiling) length:	86 mm
Installation opening (wall/ceiling) width:	39 mm
Dimension A:	120 mm
Dimension B:	61 mm
Measurement value C:	26.5 mm
Cover for box/housing/casing Ø:	86x39 mm
Borehole distance X:	103 mm
Borehole distance Y:	32 mm

Connections / Entries

clamp technology: Lamella technology

Safety / Properties

Flammability: Self-extinguishing according to UL 94 V-0

Features

Properties:	Halogen and silicone free
Thread type:	metric
Thread length:	short

Approvals / Certifications

Protection class: IP66

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	155 °C

Thanks to the various cable grommets available, the divisible frames of the 1910 series allow cables with or without plugs with diameters from 2 to 35 mm to be fed through. The side closure of the frame provides strain relief and water protection. The opening grommets can be freely positioned within the frame. Protection class IP66 or NEMA 4X can be achieved with any combination of grommets (single, double, quadruple, break-out, large). The overmoulded seal and thus the complete V0 self-extinguishing of the system make the 1910 series a unique product.



Assembly instructions



Planning data

Product datasheet:

- Multiple configurations in the same frame
- Fixing screws in steel AISI304
- degree of protection IP66 and NEMA 4X (indoor)
- High pull-out forces according to EN 62444
- Robust construction IK10
- overmolded gasket acc. to UL 94 V-0
- Colour black