

Product datasheet:

Splittable Frame, low profile, 4 passages

Divisible frame Series 1911 low profile for cables with and without connectors

· A set of 2 stainless steel AISI304 fastening screws with black dacromet finishing



Article number:  **1911.L4**

EAN: 7611614496924

Packaging quantity: 10

Price group: 580

Dimensions / Form

Installation opening (wall/ceiling) length: 86 mm

Installation opening (wall/ceiling) width: 18 mm

Dimension A: 120 mm

Dimension B: 41 mm

Measurement value C: 26 mm

Cover for box/housing/casing Ø: 86x18 mm

Borehole distance X: 103 mm

Safety / Properties

Flammability: Self-extinguishing according to UL 94 V-0

Features

Properties: Halogen and silicone free

Approvals / Certifications

Protection class: IP66

Storage / Installation / Operation

Minimum operating temperature: -40 °C

Maximum operating temperature: 155 °C

The 1911-low profile cable entry system consists of a splittable frame designed to accommodate small (1919.SPP) grommets for cables with or without connectors. With all combinations of grommets, e.g. single, double and quadruple, IP66 and NEMA 4X* are guaranteed. The overmolded gasket guarantees faster installation times and the complete V0 self-extinguishing of the system.

- for small 1919.SPP grommets
- Fixing screws in steel AISI304
- IP66 certified, Nema 4X* with any combination of grommets
- High pull-out forces according to EN 62444
- Robust construction IK10
- overmolded gasket acc. to UL 94 V-0
- Colour black



Assembly instructions



Planning data