

Product datasheet:

Splittable Frame, low profile, rear installation, 4 passages

Divisible frame Series 1912.Lx.FT low profile for rear mounting

Article number:	➔ 1912.L4.FT
EAN:	7611614499659
Packaging quantity:	10
Price group:	580

Dimensions / Form

Installation opening (wall/ceiling) length:	86 mm
Installation opening (wall/ceiling) width:	18 mm
Dimension A:	120 mm
Dimension B:	41.4 mm
Measurement value C:	26.5 mm
Cover for box/housing/casing Ø:	86x18 mm
Borehole distance X:	103 mm

Safety / Properties

Flammability:	Self-extinguishing according to UL 94 V-0
---------------	---

Features

Properties:	Halogen and silicone free
-------------	---------------------------

Approvals / Certifications


Protection class:	IP66
-------------------	------

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	155 °C

The 1912.Lx.FT low profile splittable frames are equipped with threaded inserts and with front taps which allow the installation on the rear part of the panel and keep the front part clean avoiding dirt accumulation. All the other technical data are exactly the same as of the 1910 standard series.

- Flat surface without dirt deposit
- rear installation with M4 threaded inserts
- High pull-out forces according to EN 62444
- Robust construction IK10
- overmolded gasket acc. to UL 94 V-0
- Colour black



Planning data