

Product datasheet:

Divisible frame Series 1913, 90° angled, size 24

Divisible frame Series 1913, 90° angled, size 24

Article number:	➡ 1913.2490
EAN:	7611614497006
Packaging quantity:	10
Price group:	580

Dimensions / Form

Installation opening (wall/ceiling) length:	112 mm
Installation opening (wall/ceiling) width:	39 mm
Dimension A:	146 mm
Dimension B:	76.3 mm
Measurement value C:	84.2 mm
Cover for box/housing/casing Ø:	112x39 mm
Borehole distance X:	130 mm
Borehole distance Y:	32 mm

Safety / Properties

Flammability:	Self-extinguishing according to UL 94 V-0
---------------	---

Features

Properties:	Halogen and silicone free
-------------	---------------------------

Approvals / Certifications


Protection class:	IP54
-------------------	------

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	155 °C

This 90° cable entry system is used when the machinery construction does not allow the straight cables entrance, or when a nice design is requested. It is suitable for both cables with or without connectors and corrugated conduits, or a mix of them. The grommets can be freely accommodated into the frame.

- 90° cable entry
- Multiple configurations in the same frame
- Frame screws in AISI304 Stainless Steel
- High pull-out forces according to EN 62444
- Robust construction IK10
- Colour black



Planning data