

Product datasheet:

Module Frame extended, 1.5 openings

Module Frame extended, size 24, 1.5 openings

· Set of 4 stainless steel AISI304 fastening screws with black Dacromet finishing



Article number:	1914.24MX15
EAN:	7611614497013
Packaging quantity:	10
Price group:	580

Dimensions / Form

Installation opening (wall/ceiling) length:	114 mm
Installation opening (wall/ceiling) width:	72 mm
Dimension A:	146 mm
Dimension B:	95 mm
Measurement value C:	26 mm
Cover for box/housing/casing Ø:	114x72 mm
Borehole distance X:	130 mm
Borehole distance Y:	32/26 mm

Safety / Properties

Flammability:	Self-extinguishing according to UL 94 V-0
---------------	---

Features

Properties:	Halogen and silicone free
-------------	---------------------------

Approvals / Certifications

Protection class:	IP54
-------------------	------

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	155 °C

The 1914.MX15 splittable frame allows up to 60 cables with or without connectors or one or two cables up to 35mm in diameter to pass through electric cabinet or machine walls. The small and big grommets can be freely positioned inside the frame. The frame is firmly closed due to three stainless steel screws on the right side.

- Multiple configurations in the same frame
- Frame screws in AISI304 Stainless Steel
- High pull-out forces according to EN 62444
- Robust construction IK10
- External gasket included
- threaded inserts version on request
- Colour black



Assembly instructions



Planning data