

Product datasheet:

Module Frame extended, 2 openings

Module Frame extended, size 16, multiple openings

· Set of 4 stainless steel AISI304 fastening screws with black Dacromet finishing



Article number:  **1914.16MX2**

EAN: 7611614497075

Packaging quantity: 1

Price group: 580

Dimensions / Form

Installation opening (wall/ceiling) length: 86 mm

Installation opening (wall/ceiling) width: 92 mm

Dimension A: 120 mm

Dimension B: 115 mm

Measurement value C: 26.4 mm

Cover for box/housing/casing Ø: 86x92 mm

Borehole distance X: 103 mm

Borehole distance Y: 32/20/32 mm

Safety / Properties

Flammability: Self-extinguishing according to UL 94 V-0

Features

Properties: Halogen and silicone free

Approvals / Certifications

Protection class: IP54

Storage / Installation / Operation

Minimum operating temperature: -40 °C

Maximum operating temperature: 155 °C

The 1914.16MXx splittable frames family is a modular solution for installations where a large quantity of cables need to be routed through electrical cabinet walls or machines. This solution is not only modular but it is also a general solution that can be adopted as main cable entry. Both, cables with or without connectors, can be routed (32 for each module) and future upgrades can easily be executed in the cheapest and fastest way.

- Multiple configurations in the same frame
- Frame screws in AISI304 Stainless Steel
- High pull-out forces according to EN 62444
- Robust construction IK10
- External gasket included
- Colour black



Assembly instructions



Planning data