

Product datasheet:

Module frame splittable, IP54, size 16

· Set of 4 stainless steel AISI304 fastening screws · with black Dacromet finishing



Article number: **1914.16M**

EAN: 7611614497020

Packaging quantity: 10

Dimensions / Form

Installation opening (wall/ceiling) length:	86 mm
Installation opening (wall/ceiling) width:	40 mm
Dimension A:	120 mm
Dimension B:	63 mm
Measurement value C:	26.4 mm
Cover for box/housing/casing Ø:	86x40 mm
Borehole distance X:	103 mm
Borehole distance Y:	32 mm

Safety / Properties

Flammability: Self-extinguishing according to UL 94 V-0

Features

Properties: Halogen and silicone free

Approvals / Certifications


Protection class: IP54

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	155 °C

The 1914.16M splittable frame series allow up to 32 cables with or without connector or one or two cables up to 35mm diameter to pass through electric cabinet or machine walls. The small and big grommets can be freely positioned inside the frame. This frame is the base structure for the expandable MX version.

- Multiple configurations in the same frame
- Frame screws in AISI304 Stainless Steel
- External gasket included
- High pull-out forces according to EN 62444
- Robust construction IK10
- Colour black



Assembly instructions



Planning data