

Product datasheet:

Divisible frame 1920.Click-Series, size 16

Divisible frame 1920.CLICK series for cables with and without connectors

· Set of 4 stainless steel AISI304 fastening screws · with black Dacromet finishing



Article number:  **1920.16.CLICK**

EAN: 7611614501581

Packaging quantity: 10

Dimensions / Form

Installation opening (wall/ceiling) length: 86 mm

Installation opening (wall/ceiling) width: 36 mm

Dimension A: 124.6 mm

Dimension B: 62.6 mm

Measurement value C: 18.6 mm

Cover for box/housing/casing Ø: 86x36 mm

Borehole distance X: 103 mm

Borehole distance Y: 32 mm

Safety / Properties

Flammability: Self-extinguishing according to UL 94 V-0

Features

Properties: Halogen and silicone free

Approvals / Certifications

Protection class: IP54

Storage / Installation / Operation

Minimum operating temperature: -40 °C

Maximum operating temperature: 155 °C

The splittable frames of the 1920.CLICK series allow to accomodate up to 40 cables with or without connectors with diameters from 2 to 31 mm. The frame closing is made through two side hooks. Despite the absence of screws, the mechanical seal on the cable is perfect. The frame accepts 10 small grommets or 1 large grommet and 6 small grommets.

- For small and large grommets (same frame)
- Without screws, snap closing
- High pull-out forces according to EN 62444
- Compact design
- External gasket included
- threaded inserts version on request
- Colour grey



Assembly instructions



Planning data