

Product datasheet:

Divisible frame 1930 series for large cables or corrugated conduits

Divisible frame 1930.380M series for large cables or corrugated conduits

Article number:	➔ 1930.380M
EAN:	7611614497105
Packaging quantity:	1

Dimensions / Form

Installation opening (wall/ceiling) length:	72 mm
Installation opening (wall/ceiling) width:	72 mm
Dimension A:	116 mm
Dimension B:	116 mm
Measurement value C:	33.5 mm
Cover for box/housing/casing Ø:	72x72 mm
Borehole distance X:	100.5 mm
Borehole distance Y:	56.5 mm

Safety / Properties

Flammability:	Self-extinguishing according to UL 94 V-0
---------------	---

Features

Properties:	Halogen and silicone free
-------------	---------------------------

Approvals / Certifications

Protection class:	IP54
-------------------	------

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	155 °C

The splittable frame of the 1930.380M series is a modular solution for large sized cables and corrugated pipe installations on electrical cabinets or machinery. The system allows cables or corrugated pipes with a diameter from 36 to 66 mm to be secured in the cabinet entrance in a fast manner, enabling a strain relief at the same time. It is the base product for increasing the number of cables thanks to the modular capabilities of the 1930.380MX system.

- Fast and easy fixing of large diameter cables and corrugated pipes
- Diameters from 36 to 65 mm
- Free installation on 4 sides
- Robust construction IK10
- no need of gasket
- Frame screws in AISI304 Stainless Steel
- Colour black



Assembly instructions



Planning data