

Product datasheet:

Divisible modular frame 1930.380MX series, 3 windows

Divisible modular frame 1930.380MX series for large cables or corrugated conduits

Article number:	➔ 1930.380MX3
EAN:	7611614497129
Packaging quantity:	1
Price group:	580

Dimensions / Form

Installation opening (wall/ceiling) length:	a mm
Installation opening (wall/ceiling) width:	.261.0 mm
Dimension A:	305.0 mm
Dimension B:	116 mm
Measurement value C:	33.5 mm
Cover for box/housing/casing Ø:	ax.261.0x72 mm

Safety / Properties

Flammability:	Self-extinguishing according to UL 94 V-0
---------------	---

Features

Properties:	Halogen and silicone free
-------------	---------------------------

Approvals / Certifications

Protection class:	IP54
-------------------	------

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	155 °C

The splittable 1930.380MX frames are used for routing large diameter cables and corrugated pipes through electric cabinets of all sorts. The solution is modular and thus easy to expand.

- Fast and easy fixing of large diameter cables and corrugated pipes
- modular system
- Diameters from 36 to 65 mm
- horizontal oder vertical installation
- no need of gasket
- Frame screws in AISI304 Stainless Steel
- Colour black



Assembly instructions



Planning data