

## Product datasheet:

# Cable glands 1925.OSF.ZIP series, splittable, snap-on mounting, M25

## Cable glands 1925.OSF.ZIP series, splittable, snap-on mounting

|                        |                     |
|------------------------|---------------------|
| <b>Article number:</b> | ⇒ 1925.OSF.ZIP.25.G |
| EAN:                   | 7611614499109       |
| Packaging quantity:    | 10                  |
| Price group:           | 580                 |

### Dimensions / Form

|                                             |         |
|---------------------------------------------|---------|
| Installation opening (wall/ceiling) length: | 25.5 mm |
| Installation opening (wall/ceiling) width:  | 25.5 mm |
| Ø A:                                        | 25.0 mm |
| Cover for box/housing/casing Ø:             | 25.5 mm |

### Safety / Properties

|               |                                           |
|---------------|-------------------------------------------|
| Flammability: | Self-extinguishing according to UL 94 V-0 |
|---------------|-------------------------------------------|

### Features

|             |                           |
|-------------|---------------------------|
| Properties: | Halogen and silicone free |
|-------------|---------------------------|

### Approvals / Certifications

|                   |      |
|-------------------|------|
| Protection class: | IP54 |
|-------------------|------|

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 130 °C |

The 1925.OSF.ZIP series is a divisible cable gland for metric holes especially designed for cables with connectors. The installation can be made only from the front since no locknut is required. It can be equipped with 1929.SPC grommets with single, double or quadruple holes from 2 to 14 mm in diameter.

- Without screws, snap closing
- snap mounting
- Wall thickness from 1.2 up to 2.0 mm
- External gasket included
- Colour grey



Assembly instructions



Planning data