

Product datasheet:

Membrane plates 1940.PDM.KN series

Membrane plates 1940.PDM.KN series

Article number:  1940.PDM.KN/19.G

EAN: 7611614500119

Packaging quantity: 10

Dimensions / Form

Installation opening (wall/ceiling) length: 192 mm

Installation opening (wall/ceiling) width: 62 mm

Dimension A: 221 mm

Dimension B: 90 mm

Measurement value C: 14 mm

Cover for box/housing/casing Ø: 192x62 mm

Borehole distance X: 2x101 mm

Borehole distance Y: 76/72 mm

Safety / Properties

Flammability: Self-extinguishing according to UL 94 V-0

Features

Properties: Halogen and silicone free

Approvals / Certifications

Protection class: IP66

Storage / Installation / Operation

Minimum operating temperature: -40 °C

Maximum operating temperature: 110 °C

The 1940.PDM.KN series consists of multiple cable entry plates that are suitable for cabinet sides or cabinet bases. The dimensions of the mounting holes are compatible with cabinets from well-known manufacturers. The cable is pushed through the initially closed front membrane, while the second membrane increases strain relief and liquid resistance.

- For up to 72 cables without connectors
- high strain relief thanks to the double membrane
- internal reinforcing frame
- cost efficient solution
- Colour grey



Assembly instructions



Planning data