

Product datasheet:

Membrane plates 1940.PDM.KN series

Membrane plates 1940.PDM.KN series

Article number:	➔ 1940.PDM.KN/72.G
EAN:	7611614500133
Packaging quantity:	1

Dimensions / Form

Installation opening (wall/ceiling) length:	192 mm
Installation opening (wall/ceiling) width:	62 mm
Dimension A:	221 mm
Dimension B:	90 mm
Measurement value C:	14 mm
Cover for box/housing/casing Ø:	192x62 mm
Borehole distance X:	2x101 mm
Borehole distance Y:	76/72 mm

Safety / Properties

Flammability:	Self-extinguishing according to UL 94 V-0
---------------	---

Features

Properties:	Halogen and silicone free
-------------	---------------------------

Approvals / Certifications

Protection class:	IP66
-------------------	------

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	110 °C

The 1940.PDM.KN series consists of multiple cable entry plates that are suitable for cabinet sides or cabinet bases. The dimensions of the mounting holes are compatible with cabinets from well-known manufacturers. The cable is pushed through the initially closed front membrane, while the second membrane increases strain relief and liquid resistance.

- For up to 72 cables without connectors
- high strain relief thanks to the double membrane
- internal reinforcing frame
- cost efficient solution
- Colour grey



Assembly instructions



Planning data