

Product datasheet:

Membrane plates 1940.PM.24 series, 50 passages

Membrane plates 1940.PM.24 series

Article number:  1940.PM.24/50.G

EAN: 7611614500270

Packaging quantity: 10

Dimensions / Form

Installation opening (wall/ceiling) length: 112 mm

Installation opening (wall/ceiling) width: 36(a mm

Dimension A: 144 mm

Dimension B: 46 mm

Measurement value C: 12 mm

Cover for box/housing/casing Ø: 112x36(ax.+0.5) mm

Assembly / Installation

Wall thickness min.: 1.5 mm

Wall thickness max.: 2.5 mm

Safety / Properties

Flammability: Self-extinguishing according to UL 94 V-0

Features

Properties: Halogen and silicone free

Approvals / Certifications

Protection class: IP65

Storage / Installation / Operation

Minimum operating temperature: -40 °C

Maximum operating temperature: 110 °C

The 1940.PM.24 series is an innovative alternative for routing cables in control cabinets and devices. The cable is pushed through the front membrane, while the second membrane increases strain relief and fluid resistance.

- For a large number of cables without connectors
- high strain relief thanks to the double membrane
- cost efficient solution
- Colour grey



UL TYPE
12



Assembly instructions



Planning data