

Product datasheet:

Round base, pyramidal cable entry plate with locknut, M32

Round base, pyramidal cable entry plate with locknut

Article number:	➔ 1940.PDP.32.G
EAN:	7611614500171
Packaging quantity:	10

Dimensions / Form

Product depth:	55.2 mm
Installation opening (wall/ceiling) length:	32.5 mm
Installation opening (wall/ceiling) width:	32.5 mm
Ø min.:	5 mm
Ø max.:	23 mm
Cover for box/housing/casing Ø:	32.5 mm

Safety / Properties

Flammability:	Self-extinguishing according to UL 94 V-0
---------------	---

Features

Properties:	Halogen and silicone free
-------------	---------------------------

Approvals / Certifications

Protection class:	IP66
-------------------	------

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	110 °C

The pyramidal cable entry plates of the 1940.PDP series are available in M25, M32, M40, M50, M63 and M75, enabling non-terminated cables with diameters from 2,5 to 64 mm to pass through the walls of e.g. an electrical cabinet. The reinforcing base plate increases the stability when large cables are being used.

- For a large selection of different diameters
- reinforcing base plate
- cost efficient solution
- UL 94 V-0
- Colour grey



Assembly instructions



Planning data