

Product datasheet:

Membrane plates 1940.PDM.C Clean series, size 24

Membrane plates 1940.PDM.24.C Clean series, size 24

Article number:	⇒ 1940.PDM24/32.C
EAN:	7611614501055
Packaging quantity:	1

Dimensions / Form

Installation opening (wall/ceiling) length:	112 mm
Installation opening (wall/ceiling) width:	36 mm
Dimension A:	155 mm
Dimension B:	66 mm
Measurement value C:	14.4 mm
Cover for box/housing/casing Ø:	112x36 mm
Borehole distance X:	130 mm
Borehole distance Y:	32 mm

Safety / Properties

Flammability:	UL 94 HB
---------------	----------

Features

Properties:	Halogen and silicone free
-------------	---------------------------

Approvals / Certifications


Protection class:	IP66
-------------------	------

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	80 °C

The 1940.PDM.24.C Clean series is mainly used in the food & pharma production thanks to the rounded shape without edges which avoids dirt accumulation and allows frequent washing. The first front membrane is lightly drilled with a small screwdriver, while the second parallel membrane acts as a reinforcement, ensuring a very high strain relief and water resistance.

- For a large number of cables without connectors
- with internal reinforcing frame
- smooth surface with rounded edge
- UL 94 HB
- Fastening optionally with snap-on or screw mounting
- Colour blue



Planning data