

Product datasheet:

Membrane plates 1940.PDM.M.C series, M32

Membrane plates 1940.PDM.M.C series

Article number:	➔ 1940.PDM.M32/4.C
EAN:	7611614501062
Packaging quantity:	10

Dimensions / Form

Product depth:	7 mm
Installation opening (wall/ceiling) length:	32.5 mm
Installation opening (wall/ceiling) width:	32.5 mm
Cover for box/housing/casing Ø:	32.5 mm

Safety / Properties

Flammability:	UL 94 HB
---------------	----------

Features

Properties:	Halogen and silicone free
-------------	---------------------------

Approvals / Certifications

Protection class:	IP66
-------------------	------

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	80 °C

The 1940.PDM.M.C Clean series is mainly used in the food&pharma production thanks to the rounded shape without edges which avoids dirt accumulation and allows frequent washing. The cable entry plate can be fixed to the panel from the inside with four hidden screws or screwed on the panel. The holes location is guided by a laser printing which guarantees the front clean area during the operation. The first front membrane is lightly drilled with a small screwdriver, while the second parallel membrane acts as a reinforcement, ensuring a very high strain relief and water resistance.

- For a large number of cables without connectors
- with internal reinforcing frame
- smooth surface with rounded edge
- UL 94 HB
- Fixing with locknut
- Colour blue



Planning data