

## Product datasheet:

# Cable glands Progress® according to EN 45545-2/3 and NFPA 130

## Long entry thread metric

- Two-piece sealing insert
- overall length insulated
- Entry thread Pg and NPT



|                        |                    |
|------------------------|--------------------|
| <b>Article number:</b> | <b>GD F1160.32</b> |
| EAN:                   | 7611614273198      |
| Packaging quantity:    | 25                 |
| Price group:           | 540                |

## Dimensions / Form

|                  |         |
|------------------|---------|
| Thread:          | M32x1.5 |
| Spanner size:    | 36 mm   |
| Dimension H:     | 28 mm   |
| Thread length L: | 13 mm   |

## Connections / Entries

|                                 |                        |
|---------------------------------|------------------------|
| Min. clamping range:            | 21 mm                  |
| Max. clamping range:            | 25.5 mm                |
| Clamping range with inlet min.: | 17 mm                  |
| Clamping range with inlet max.: | 21 mm                  |
| clamp technology:               | Compression technology |

## Features

|                |        |
|----------------|--------|
| Thread type:   | metric |
| Thread length: | long   |

## Approvals / Certifications

|                                  |                       |
|----------------------------------|-----------------------|
| Protection class:                | IP69                  |
| Protection class with condition: | IP 68 (10 bar) / IP69 |

## Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -50 °C |
| Maximum operating temperature: | 105 °C |



Assembly instructions



Planning data