

Product datasheet:

Cable glands Progress® according to EN 45545-2/3 and NFPA 130 EMC powerCONNECT nickel-plated brass

Short entry thread metric

- Two-piece sealing insert
- not overall length insulated
- 1 = One-piece sealing insert
- Stainless steel A2 or A4
- Entry thread Pg and NPT



Article number: **GD F1084.40**

EAN: 7611614312798

Packaging quantity: 10

Price group: 520


Dimensions / Form

Thread: M40x1.5

Spanner size: 46 mm

Dimension H: 42 mm

Thread length L: 8 mm



Connections / Entries

Min. clamping range: 28.5 mm

Max. clamping range: 33 mm

Clamping range with inlet min.: 24 mm

Clamping range with inlet max.: 28.5 mm

clamp technology: Compression technology

Contact: Press sleeve

Features

Properties: For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance. Compact design

Thread type: metric

Thread length: short

Approvals / Certifications

Protection class: IP69

Protection class with condition: IP 68 (10 bar) / IP69

Storage / Installation / Operation

Minimum operating temperature: -50 °C



Assembly instructions



Certificates



Planning data

Product datasheet:

Maximum operating temperature: 105 °C
