

Product datasheet:

Cable glands Progress® according to EN 45545-2/3 and NFPA 130 EMC powerCONNECT nickel-plated brass

Long entry thread metric

- Two-piece sealing insert
- not overall length insulated
- 1 = One-piece sealing insert
- Stainless steel A2 or A4
- Entry thread Pg and NPT



Article number:	➤ F1184.32
EAN:	7611614312873
Packaging quantity:	25

Dimensions / Form

Thread:	M32x1.5
Spanner size:	36 mm
Dimension H:	38.5 mm
Thread length L:	13 mm

Connections / Entries

Min. clamping range:	21 mm
Max. clamping range:	25.5 mm
Clamping range with inlet min.:	17 mm
Clamping range with inlet max.:	21 mm
clamp technology:	Compression technology
Contact:	Press sleeve

Features


Properties:	For high leakage currents, concentric 360° shield contact ensure extremely low transfer resistance and transfer impedance. Compact design
Thread type:	metric
Thread length:	long

Approvals / Certifications

Protection class:	IP69
Protection class with condition:	IP 68 (10 bar) / IP69

Storage / Installation / Operation

Minimum operating temperature:	-50 °C
Maximum operating temperature:	105 °C



Assembly instructions



Certificates



Planning data