

Product datasheet:

AGRO cable glands Ex Compact nickel-plated brass Ex d IIC and Ex e II

Entry thread metric

Approval type: EX Compact M5

- One-piece sealing insert
- not overall length insulated
- Stainless steel A2 or A4



Article number:	EX1126.25.180
EAN:	7611614242316
Packaging quantity:	20
Price group:	530

Dimensions / Form

Thread:	M25x1.5
Spanner size:	32 mm
Dimension H:	28 mm
Thread length L:	12 mm

Connections / Entries

Min. clamping range:	12.5 mm
Max. clamping range:	18 mm
clamp technology:	Compression technology

Features


Thread type:	metric
--------------	--------

Approvals / Certifications

Protection class:	IP67
Protection class with condition:	IP 66 - IP 68 (30 bar)
Explosion-proof design:	Yes
EX zone:	Gas 1 and 2 - Dust 21 and 22
Gas:	II 2G Ex db eb IIC Gb
Dust:	II 2D Ex ta IIIC
Test standard:	IEC EN 60079-7
IECEx certification:	IECEx PTB 12.0055X
Further certifications:	PTB 10 ATEX 1034X
Connectivity certification:	PTB 10 ATEX 1034X

Storage / Installation / Operation

Minimum operating temperature:	-60 °C
Maximum operating temperature:	105 °C



Assembly instructions



Certificates



Planning data