

## Product datasheet:

# AGRO cable glands Progress® nickel-plated brass increased safety Ex e II

## Short entry thread Pg

### Approval type: Progress MS EX

- One-piece sealing insert
- not overall length insulated
- Executions in steel A2 and A4, entry thread NPT



|                        |                      |
|------------------------|----------------------|
| <b>Article number:</b> | <b>EX1000.07.065</b> |
| EAN:                   | 7611614176369        |
| Packaging quantity:    | 50                   |
| Price group:           | 530                  |

### Dimensions / Form

|                  |       |
|------------------|-------|
| Thread:          | Pg 7  |
| Spanner size:    | 15 mm |
| Dimension H:     | 17 mm |
| Thread length L: | 6 mm  |

### Connections / Entries

|                      |                        |
|----------------------|------------------------|
| Min. clamping range: | 5 mm                   |
| Max. clamping range: | 6.5 mm                 |
| clamp technology:    | Compression technology |

### Features

|                |       |
|----------------|-------|
| Thread type:   | Pg    |
| Thread length: | short |

### Approvals / Certifications

|                                  |                              |
|----------------------------------|------------------------------|
| Protection class:                | IP66                         |
| Protection class with condition: | IP 66 - IP 68 (10 bar)       |
| Explosion-proof design:          | Yes                          |
| EX zone:                         | Gas 1 and 2 - Dust 21 and 22 |
| Gas:                             | II 2G Ex eb IIC Gb           |
| Dust:                            | II 2D Ex tb IIIC Db          |
| Test standard:                   | IEC EN 60079-7               |
| IECEx certification:             | IECEx SEV 15.0019X           |
| Further certifications:          | SEV 15 ATEX 0152X            |
| Connectivity certification:      | SEV 15 ATEX 0152X            |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -60 °C |
|--------------------------------|--------|



Assembly instructions



Certificates



Planning data

## Product datasheet:

Maximum operating temperature: 100 °C

---