

## Product datasheet:

# AGRO cable glands Progress® nickel-plated brass increased safety Ex e II for installation of multiple cables

## Short entry thread Pg

### Approval type: Progress MS Multi EX

- One-piece sealing insert
- not overall length insulated
- 3 = Material sealing insert NBR
- Suitable locking pins see accessories
- Executions in steel A2 and A4, entry thread NPT



**Article number:** **EX1310.21.4.070**

**EAN:** 7611614239491

**Packaging quantity:** 25

### Dimensions / Form

|                 |       |
|-----------------|-------|
| Thread:         | Pg 21 |
| Product length: | 7 mm  |
| Spanner size:   | 30 mm |
| Dimension H:    | 28 mm |
| Dimension L:    | 7 mm  |

### Connections / Entries

|                      |                        |
|----------------------|------------------------|
| Min. clamping range: | 5.5 mm                 |
| Max. clamping range: | 7 mm                   |
| clamp technology:    | Compression technology |

### Features

|                |       |
|----------------|-------|
| Thread type:   | Pg    |
| Thread length: | short |

### Approvals / Certifications

|                             |                              |
|-----------------------------|------------------------------|
| Protection class:           | IP66                         |
| Explosion-proof design:     | Yes                          |
| EX zone:                    | Gas 1 and 2 - Dust 21 and 22 |
| Gas:                        | II 2G Ex eb IIC Gb           |
| Dust:                       | II 2D Ex tb IIIC Db          |
| Test standard:              | IEC EN 60079-7               |
| IECEx certification:        | IECEx SEV 15.0019X           |
| Further certifications:     | SEV 15 ATEX 0152X            |
| Connectivity certification: | SEV 15 ATEX 0152X            |



Assembly instructions



Certificates



Planning data

## Product datasheet:

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -60 °C |
| Maximum operating temperature: | 100 °C |