

Product datasheet:

AGRO cable glands Progress® nickel-plated brass with clamps increased safety Ex e II

Short entry thread Pg

Approval type: Progress MS KB EX

- Two-piece sealing insert
- not overall length insulated
- 1 = One-piece sealing insert
- 2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X
- Long entry thread
- Executions in steel A2 and A4



Article number: EX1803.07.03.065

EAN: 7611614176666

Packaging quantity: 50

Price group: 530


Dimensions / Form

Thread: Pg 7

Spanner size: 15/16 mm

Dimension H: 26 mm

Thread length L: 6 mm



Connections / Entries

Min. clamping range: 5 mm

Max. clamping range: 6.5 mm

clamp technology: Compression technology

Features

Thread type: Pg

Thread length: short

Approvals / Certifications

Protection class: IP66

Protection class with condition: IP 66 - IP 68 (10 bar)

Explosion-proof design: Yes

EX zone: Gas 1 and 2 - Dust 21 and 22

Gas: II 2G Ex eb IIC Gb

Dust: II 2D Ex tb IIIC Db

Test standard: IEC EN 60079-7

IECEx certification: IECEx SEV 15.0018

Further certifications: SEV 15 ATEX 0151



Assembly instructions



Certificates



Planning data

Product datasheet:

Connectivity certification: SEV 15 ATEX 0151

Storage / Installation / Operation

Minimum operating temperature: -60 °C

Maximum operating temperature: 100 °C
