

Product datasheet:

AGRO cable glands Progress® EMC Rapid nickel-plated brass with contact disc increased safety EX e II

Short entry thread metric

Approval type: Progress MS EMC Rapid EX

- One-piece sealing insert
- not overall length insulated
- Long entry thread available on request



Article number: EX1081.25.190

EAN: 7611614211794

Packaging quantity: 25

Dimensions / Form

Thread:	M25x1.5
Spanner size:	30 mm
Dimension H:	33 mm
Thread length L:	7 mm

Connections / Entries

Min. clamping range:	17 mm
Max. clamping range:	19 mm
clamp technology:	Compression technology
Contact:	contact plate


Features

Properties: For a quick installation of partially dismantled cables as well as thoroughly shielded cables

Thread type:	metric
Thread length:	short

Approvals / Certifications

Protection class:	IP66
Protection class with condition:	IP 66 - IP 68 (10 bar)
Explosion-proof design:	Yes
EX zone:	Gas 1 and 2 - Dust 21 and 22
Gas:	II 2G Ex eb IIC Gb
Dust:	II 2D Ex tb IIIC Db
Test standard:	IEC EN 60079-7
IECEx certification:	IECEx SEV 15.0019X
Further certifications:	SEV 15 ATEX 0152X



Assembly instructions



Certificates



Planning data

Product datasheet:

Connectivity certification:

SEV 15 ATEX 0152X

Storage / Installation / Operation

Minimum operating temperature:

-60 °C

Maximum operating temperature:

100 °C
