

Product datasheet:

AGRO cable glands Progress® EMC Rapid nickel-plated brass with contact disc increased safety EX e II

Short entry thread metric

Approval type: Progress MS EMC Rapid EX

- One-piece sealing insert
- not overall length insulated
- Long entry thread available on request



Article number: EX1081.32.210

EAN: 7611614211800

Packaging quantity: 25

Price group: 530

Dimensions / Form

Thread: M32x1.5

Spanner size: 36 mm

Dimension H: 32 mm

Thread length L: 8 mm

Connections / Entries

Min. clamping range: 18 mm

Max. clamping range: 21 mm

clamp technology: Compression technology

Contact: contact plate

Features

Properties: For a quick installation of partially dismantled cables as well as thoroughly shielded cables

Thread type: metric

Thread length: short

Approvals / Certifications

Protection class: IP66

Protection class with condition: IP 66 - IP 68 (10 bar)

Explosion-proof design: Yes


EX zone: Gas 1 and 2 - Dust 21 and 22

Gas: II 2G Ex eb IIC Gb

Dust: II 2D Ex tb IIIC Db

Test standard: IEC EN 60079-7

IECEx certification: IECEx SEV 15.0019X



Assembly instructions



Certificates



Planning data

Product datasheet:

Further certifications:	SEV 15 ATEX 0152X
Connectivity certification:	SEV 15 ATEX 0152X

Storage / Installation / Operation

Minimum operating temperature:	-60 °C
Maximum operating temperature:	100 °C