

## Product datasheet:

# AGRO cable glands Progress® EMC Rapid nickel-plated brass with contact disc increased safety EX e II

## Short entry thread Pg

### Approval type: Progress MS EMC Rapid EX

- One-piece sealing insert
- not overall length insulated
- Long entry thread available on request



**Article number:** EX1081.11.120

**EAN:** 7611614211961

**Packaging quantity:** 50

### Dimensions / Form

|                  |       |
|------------------|-------|
| Thread:          | Pg 11 |
| Spanner size:    | 21 mm |
| Dimension H:     | 25 mm |
| Thread length L: | 6 mm  |

### Connections / Entries

|                      |                        |
|----------------------|------------------------|
| Min. clamping range: | 8.5 mm                 |
| Max. clamping range: | 12 mm                  |
| clamp technology:    | Compression technology |
| Contact:             | contact plate          |


### Features

**Properties:** For a quick installation of partially dismantled cables as well as thoroughly shielded cables

|                |       |
|----------------|-------|
| Thread type:   | Pg    |
| Thread length: | short |

### Approvals / Certifications

|                                  |                              |
|----------------------------------|------------------------------|
| Protection class:                | IP66                         |
| Protection class with condition: | IP 66 - IP 68 (10 bar)       |
| Explosion-proof design:          | Yes                          |
| EX zone:                         | Gas 1 and 2 - Dust 21 and 22 |
| Gas:                             | II 2G Ex eb IIC Gb           |
| Dust:                            | II 2D Ex tb IIIC Db          |
| Test standard:                   | IEC EN 60079-7               |
| IECEx certification:             | IECEx SEV 15.0019X           |
| Further certifications:          | SEV 15 ATEX 0152X            |



Assembly instructions



Certificates



Planning data

## Product datasheet:

Connectivity certification: SEV 15 ATEX 0152X

---

### **Storage / Installation / Operation**

---

Minimum operating temperature: -60 °C

---

Maximum operating temperature: 100 °C

---