

Product datasheet:

AGRO EMC cable glands Progress® nickel-plated brass with contact sleeve increased safety Ex e II

Short entry thread Pg

Approval type: Progress MS EMC EX

- One-piece sealing insert
- not overall length insulated
- Long entry thread available on request



Article number: EX1080.29.230

EAN: 7611614178707

Packaging quantity: 25

Dimensions / Form

Thread:	Pg 29
Spanner size:	38 mm
Dimension H:	33 mm
Thread length L:	8 mm

Connections / Entries

Min. clamping range:	19 mm
Max. clamping range:	23 mm
clamp technology:	Compression technology
Contact:	Contact sleeve


Features

Properties: Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland

Thread type:	Pg
Thread length:	short

Approvals / Certifications

Protection class:	IP66
Protection class with condition:	IP 66 - IP 68 (10 bar)
Explosion-proof design:	Yes
EX zone:	Gas 1 and 2 - Dust 21 and 22
Gas:	II 2G Ex eb IIC Gb
Dust:	II 2D Ex tb IIIC Db
Test standard:	IEC EN 60079-7
IECEx certification:	IECEx SEV 15.0019X
Further certifications:	SEV 15 ATEX 0152X



Assembly instructions



Certificates

Product datasheet:

Connectivity certification:

SEV 15 ATEX 0152X

Storage / Installation / Operation

Minimum operating temperature:

-60 °C

Maximum operating temperature:

100 °C
