

## Product datasheet:

# AGRO synthetic cable glands Progress® GFK increased safety Ex e II

## Entry thread Pg

### Approval type: Progress GFK EX

- Light grey RAL 7035
- One-piece sealing insert
- 3 = Material sealing insert NBR



|                        |                      |
|------------------------|----------------------|
| <b>Article number:</b> | <b>EX1571.16.080</b> |
| EAN:                   | 7611614178875        |
| Packaging quantity:    | 50                   |
| Price group:           | 530                  |

### Dimensions / Form

|                  |       |
|------------------|-------|
| Thread:          | Pg 16 |
| Spanner size:    | 27 mm |
| Dimension H:     | 28 mm |
| Thread length L: | 13 mm |

### Connections / Entries

|                      |                        |
|----------------------|------------------------|
| Min. clamping range: | 6 mm                   |
| Max. clamping range: | 8 mm                   |
| clamp technology:    | Compression technology |

### Features


|              |              |
|--------------|--------------|
| Properties:  | halogen-free |
| Thread type: | Pg           |

### Approvals / Certifications

|                             |                              |
|-----------------------------|------------------------------|
| Protection class:           | IP66                         |
| Explosion-proof design:     | Yes                          |
| EX zone:                    | Gas 1 and 2 - Dust 21 and 22 |
| Gas:                        | II 2G Ex eb IIC Gb           |
| Dust:                       | II 2D Ex tb IIIC Db          |
| Test standard:              | IEC EN 60079-7               |
| IECEx certification:        | IECEx SEV 15.0019X           |
| Further certifications:     | SEV 15 ATEX 0152X            |
| Connectivity certification: | SEV 15 ATEX 0152X            |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -20 °C |
| Maximum operating temperature: | 85 °C  |



Assembly instructions



Certificates



Planning data