

Product datasheet:

AGRO synthetic cable glands Progress® GFK increased safety Ex e II

Entry thread Pg

Approval type: Progress GFK EX

- Black RAL 9005
- One-piece sealing insert
- 3 = Material sealing insert NBR



Article number:	EX1540.09.060
EAN:	7611614177830
Packaging quantity:	50

Dimensions / Form

Thread:	Pg 9
Spanner size:	21 mm
Dimension H:	26 mm
Thread length L:	12 mm

Connections / Entries

Min. clamping range:	4.5 mm
Max. clamping range:	6 mm
clamp technology:	Compression technology

Features


Properties:	halogen-free
Thread type:	Pg

Approvals / Certifications

Protection class:	IP66
Explosion-proof design:	Yes
EX zone:	Gas 1 and 2 - Dust 21 and 22
Gas:	II 2G Ex eb IIC Gb
Dust:	II 2D Ex tb IIIC Db
Test standard:	IEC EN 60079-7
IECEx certification:	IECEx SEV 15.0019X
Further certifications:	SEV 15 ATEX 0152X
Connectivity certification:	SEV 15 ATEX 0152X

Storage / Installation / Operation

Minimum operating temperature:	-20 °C
Maximum operating temperature:	85 °C



Assembly instructions



Certificates



Planning data