

Product datasheet:

AGRO synthetic cable glands Progress® GFK for increased safety Ex e II with sealing insert for multiple cables

Entry thread Pg

Approval type: Progress GFK Multi EX

- Light grey RAL 7035
- One-piece sealing insert
- 3 = Material sealing insert NBR



Article number: EX1571.16.6.030

EAN: 7611614239859

Packaging quantity: 50

Dimensions / Form

Thread:	Pg 16
Product length:	13 mm
Spanner size:	27 mm
Dimension H:	28 mm
Dimension L:	13 mm

Connections / Entries

Min. clamping range:	2.5 mm
Max. clamping range:	3 mm
clamp technology:	Compression technology

Features


Properties:	halogen-free
Thread type:	Pg

Approvals / Certifications

Protection class:	IP66
Explosion-proof design:	Yes
EX zone:	Gas 1 and 2 - Dust 21 and 22
Gas:	II 2G Ex eb IIC Gb
Dust:	II 2D Ex tb IIIC Db
Test standard:	IEC EN 60079-7
IECEx certification:	IECEx SEV 15.0019X
Further certifications:	SEV 15 ATEX 0152X
Connectivity certification:	SEV 15 ATEX 0152X

Storage / Installation / Operation

Minimum operating temperature:	-20 °C
--------------------------------	--------



Assembly instructions



Certificates



Planning data

Product datasheet:

Maximum operating temperature:

85 °C