

Product datasheet:

AGRO synthetic cable glands Progress® GFK for increased safety Ex e II with sealing insert for multiple cables

Entry thread Pg

Approval type: Progress GFK Multi EX

- Black RAL 9005
- One-piece sealing insert
- 3 = Material sealing insert NBR



Article number: EX1540.13.3.040

EAN: 7611614239965

Packaging quantity: 50

Price group: 530

Dimensions / Form

Thread: Pg 13

Product length: 13 mm

Spanner size: 27 mm

Dimension H: 28 mm

Dimension L: 13 mm

Connections / Entries

Min. clamping range: 2.5 mm

Max. clamping range: 4 mm

clamp technology: Compression technology

Features

Properties: halogen-free

Thread type: Pg

Approvals / Certifications

Protection class: IP66

Explosion-proof design: Yes

EX zone: Gas 1 and 2 - Dust 21 and 22

Gas: II 2G Ex eb IIC Gb


Dust: II 2D Ex tb IIIC Db

Test standard: IEC EN 60079-7

IECEx certification: IECEx SEV 15.0019X

Further certifications: SEV 15 ATEX 0152X

Connectivity certification: SEV 15 ATEX 0152X



Assembly instructions



Certificates



Planning data

Product datasheet:

Storage / Installation / Operation

Minimum operating temperature:	-20 °C
Maximum operating temperature:	85 °C