

Product datasheet:

AGRO synthetic cable glands Progress® GFK for increased safety Ex e II with sealing insert for multiple cables

Entry thread Pg

Approval type: Progress GFK Multi EX

- Black RAL 9005
- One-piece sealing insert
- 3 = Material sealing insert NBR



Article number: EX1540.48.6.120

EAN: 7611614240053

Packaging quantity: 5

Price group: 530

Dimensions / Form

Thread: Pg 48

Product length: 16 mm

Spanner size: 70 mm

Dimension H: 46 mm

Dimension L: 16 mm

Connections / Entries

Min. clamping range: 11 mm

Max. clamping range: 12 mm

clamp technology: Compression technology

Features

Properties: halogen-free

Thread type: Pg

Approvals / Certifications

Protection class: IP66

Explosion-proof design: Yes

EX zone: Gas 1 and 2 - Dust 21 and 22

Gas: II 2G Ex eb IIC Gb


Dust: II 2D Ex tb IIIC Db

Test standard: IEC EN 60079-7

IECEx certification: IECEx SEV 15.0019X

Further certifications: SEV 15 ATEX 0152X

Connectivity certification: SEV 15 ATEX 0152X



Assembly instructions



Certificates



Planning data

Product datasheet:

Storage / Installation / Operation

Minimum operating temperature:	-20 °C
Maximum operating temperature:	85 °C