

## Product datasheet:

# Locking plugs nickel-plated brass increased safety Ex e II

## Short entry thread metric

### Approval type: Verschlusszapfen MS EX

- with O-ring
- 1 = Metric coarse-pitch thread (with VDE Testreport)
- Long entry thread
- Executions in steel A2 and A4

**Article number:** **EX8717.08**

E-No: 126233400

EAN: 7611614175522

Packaging quantity: 50

### Dimensions / Form

Product Ø: 19 mm

Thread: M16x1.5

Dimension H: 3 mm

Thread length L: 5 mm

### Connections / Entries

clamp technology: Compression technology

### Features

Thread type: metric

Thread length: short

### Approvals / Certifications

Protection class: IP66

Explosion-proof design: Yes

EX zone: Gas 1 and 2 - Dust 21 and 22

Gas: II 2G Ex eb IIC Gb

Dust: II 2D Ex tb IIIC Db

Test standard: IEC EN 60079-7

IECEx certification: IECEx SEV 15.0018


Further certifications: SEV 15 ATEX 0151

Connectivity certification: SEV 15 ATEX 0151

### Storage / Installation / Operation

Minimum operating temperature: -60 °C

Maximum operating temperature: 100 °C



Assembly instructions



Certificates



Planning data